

DIN series high precision BA seamless steel tube

Our products have six main characteristics:

No oxidation layer on the outer and inner walls
 High precision
 No distortion after cold bending

No leakage under high pressure
 High cleanness
 No crack under flaring and flattening

Tube used in Hydraulic system

Main Norm

DIN2391-94/C DIN2445 EN10305

Tube used in Engineering machinery

Main Steel Grade

St37.4 St35 (E235)St45 (E255)St52 (E355)

Tube used in Automobile industry

Delivery Condition

NBK(+N) BK(+C) GBK(+A)

Tube used in Machine Tool industry

Table of usual dimensions in stock

Size	Kinds of tubes		
	Cold Drawing BA Steel Tube	Black Phosphated	Cold Rolled BA Steel Tube
4×0.5	√		√
4.5×0.75			√
5×1.0	√		
6×1.0	√	√	√
6×1.5	√	√	
6×2.0	√		
6×2.15	√		
6.35×0.89			√
6.35×1.6	√		
6.35×2.0	√		
6.35×2	√		
6.35×1.6	√		
6.35×1.5	√		

7.94×0.89			√
8×0.8			√
8×1.0	√	√	√
8×1.5	√	√	
8×2.0	√		
8×2.5	√		
8.6×0.9			√
8.65×0.9			√
9×1.0			√
9×1.5	√		
9.53×0.89			√
10×1.0	√	√	√
10×1.5	√	√	
10×2.0	√	√	
10×3.5	√		
12×1.0	√	√	√
12×1.5	√	√	√
12×2.0	√	√	
12×2.5	√	√	
12.7×1.0	√		
12.7×1.22	√		
12.7×1.24			
12.7×1.3	√		√
12.7×1.5	√		
12.7×1.65	√		
12.7×1.8	√		
13×0.8			√
13×1.0	√		
13×4.5	√		
14×1.0	√		√
14×1.5	√	√	
14×2.0	√	√	
14×3.0	√		
15×1.0	√		√
15×1.5	√	√	
15×2.0	√	√	
15×2.5	√	√	
15×3.0	√		
16×1.0	√		
16×1.5	√	√	
16×2.0	√	√	

16×2.5	√	√	
16×3.0	√		
18×0.8			√
18×1.0	√		
18×1.5	√	√	√
18×2.0	√	√	
18×2.5	√	√	
18×3.0	√	√	√
18×3.2			√
19.05×1.9	√		
20×1.0	√	√	
20×1.5	√	√	
20×2.0	√	√	
20×2.5	√	√	
20×3.0	√	√	
20×3.5	√		
20×4.0	√		
20.4×2.2	√		
21×3.2	√		
22×1.0	√		
22×1.5	√	√	
22×2.0	√	√	
22×2.5	√	√	
22×3.0	√	√	
22×3.2			
22×3.5	√		
22×4.0	√		
22×5.0	√		
22.7×1.25	√		
24×1.0			√
24×2.0	√		
25×2.0	√	√	
25×2.5	√	√	
25×3.0	√	√	
25×3.5			√
25×4.0	√	√	
25.4×1.65			√
27×3.0	√		
27×3.2	√		
27×3.5	√		
27×4.0	√		
28×2.0	√	√	√
28×2.5	√	√	
28×3.0	√	√	
28×3.5	√		

28×4.0	√	√	
28×6.0			√
30×2.0	√		
30×2.5	√		
30×3.0	√	√	
30×3.5	√	√	
30×4.0	√	√	
30×5.0	√		
31.75×1.65			√
31.8×1	√		√
32×2.0	√	√	
32×2.5	√	√	
32×3.0	√	√	
32×4.0	√		
34×2.0	√		
34×2.5	√		
34×3.0	√		
34×3.5	√		
34×4.0	√	√	
34×4.5	√		
34×5.0	√		
35×1.5	√		
35×2.0	√	√	
35×2.5	√		
35×3.0	√	√	
35×3.5	√	√	
35×4.0	√	√	
35×4.5	√	√	
38×2.5	√	√	
38×3.0	√	√	
38×3.5	√	√	
38×4.0	√	√	
38×5.0	√	√	
38×6.0	√		
38.1×2.0			√
38.1×2.032			√
38.1×2.41			√
40×4.0	√		
40×5.25	√		

42×1.2	√		
42×2.0	√	√	
42×2.6			
42×3.0	√	√	
42×3.5	√		
42×4.0	√	√	
42×4.5	√		
42×5.0	√	√	
42×6.0	√		
45×1.0			√
45×1.5			√
45×3.0	√	√	
45×5.0	√		
45×6.0	√		
47×5.25	√		
48×2.6	√		
48×3.0	√	√	
48×3.5	√		
48×5.0	√	√	
50×2.5	√		
50×5.0	√		√
50×6.0	√		
50.8×2.0			√
50.8×2.032			√
50.8×2.41			√
51×2.0			√
54×4.0	√		
56×1.5			√
57×1.8	√		
60×1.5			√
60×3.0			√
60×3.5	√		
60×5.0	√		√
60×6.0	√		
60×8.0	√		
63×6.5	√		
63.5×2.0	√		
63.5×5.0	√		
63.5×5.3	√		
72×4.5			√
74×2.9	√		
74×3.0	√		

75×3.0	√		
75×5.5	√		
76×2.9	√		
76×4.0	√		
80×2.0	√		
89×3.2	√		
89×4.5			√
100×2.0			√
102×2.0			√
108×5.0			√
114×3.6	√		
120×2.5			√

Tel: 0086-21-57597455 57596989

Website: www.steeltube-cn.com

E-mail: shtyb@steeltube-cn.com

Fax: 0086-21-57596916

Post Code: 201407

Address: No.4638 Jinqian Road, Qianqiao,
Fengxian, Shanghai, China